

USB Type-C™ CX Series

TYPE			Par No.	3 D Image	Size (W×H×D)	TID No.	Features	STATUS	
Connector	Soldering Style	Mounting Type							
Plug (Unit)	SMT	Paddle Card	CX60-24S-UNIT		8.25×2.4×11.1	5,200,000,291	Slim type	Mass Production	
Plug (Shell)	-	-	CX60-SLDA		10.25×4.40×23.35	-	Slim type	Mass Production	
Plug (Harness)	-	-	CX60-24S-1000-C		C to C 1m	5,220,000,534	Slim type	Mass Production	
Receptacle	Right Angle Hybrid (SMT-THT)	Mid Mount	CX70M-24P1		11.4×3.66×8.35	5,200,000,077	USB3.0 Rev1.0 5Gbps data transfer Space saving type, Depth : 8.35mm	Mass Production	
			CX70M-24P2		11.4×3.66×7.95	TBD	USB3.0 Rev1.0 5Gbps data transfer Space saving type, Depth : 7.95mm	Mass Production	
	Right Angle SMT (Dual Row)	Mid Mount	On Board	CX90B1-24P		8.94×3.14×8.15	5,200,000,499	USB3.1 Gen2 10Gbps data transfer	Mass Production
				CX90M-16P		11.0×2.96×6.55	TBD	USB2.0 480Mbps High current capable up to 6A	Mass Production
				CX90MWD2-24P		11.6×3.46×8.35	TBD	USB3.0 Rev1.0 5Gbps data transfer Waterproof : IPX8	Mass Production
	Straight SMT	Vertical	CX80B1-24P		8.94×6.5×3.14	5,200,000,701	USB3.1 Gen2 10Gbps data transfer Low profile type	Mass Production	